

## dekorform Profile Wrapped Products Care

Your dekorform products are manufactured in Australia using the highest quality materials and designed to provide years of trouble free service.

Care should be taken to wipe up spills immediately, ensuring the products are not exposed to high or continuous levels of moisture, steam and humidity.

### General Cleaning

Wipe down regularly using a damp soft cloth containing warm, soapy water.

For more stubborn stains, use a mild household spray to wipe down the door or panel with a soft cloth taking care not to rub too hard. Dry using a soft cloth so as not to leave any residue on the product.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use. It is highly recommended to test a small inconspicuous area before proceeding.

To ensure that your dekorform warranty will not be void:

DO NOT use any of the following on dekorform wrapped products: Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids and Alkalis, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Acetone, Easy-Off BAM!, M.E.K. or any other cleaning agents containing organic solvents or the above mentioned products.

Avoid contact with sharp implements. Where products are installed in a kitchen environment use range hoods whenever cooking, to avoid steam and cooking oil vapours from adversely effecting surfaces.

Failure to follow the above care instructions may result in damage to your dekorform product and void your entitlement to any warranty. dekorform warranty does not cover wear and tear.

For more information refer to dekorform Products Limited Warranty Terms & Conditions available at [www.dekorform.com.au](http://www.dekorform.com.au)

## Storage & Handling

It is important that your dekorform products are stored and handled safely with consideration and care. The following recommendations should be adhered to ensure your products are kept in good condition prior to and during fabrication.

- Store in a dry space that is protected from sun, wind and rain to minimize any rapid change in temperature and humidity. The space must be free from debris and airborne contaminants.
- Packs should be kept away from potential physical and mechanical damage.
- To avoid staining and fading, dekorform products should not be exposed to the weather while awaiting fabrication and installation.
- Keep all working surfaces free from contaminants e.g. dust, oil, adhesive, abrasive surfaces or grit that could potentially scratch or mark the decorative overlays and surface finishes.
- Pre-conditioning of the product is recommended so that it achieves the equilibrium moisture content before fixing to reduce likelihood of bowing or dimensional changes.
- Packs should be evenly supported using bearers at not more than 600mm spacing. Packs stacked on top of each other must have all the bearers vertically aligned

